Safety Data Sheet



Revision Number: 007.0 Issue date: 09/07/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI 9.5OZ QDMAX001SLNWHT 12CC Product type/use: Joint sealant, polymer silan-modified

Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067 **IDH number:** 1868684

Region: United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A

PICTOGRAM(S)



Precautionary Statements

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face

protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

contaminated clothing.

Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Limestone	1317-65-3	50 - 60	
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	68515-49-1	5 - 10	
Benzene, mono-C10-13-alkyl derivs.	129813-58-7	1 - 5	
Trimethoxyvinylsilane	2768-02-7	1 - 5	
Benzene, mono-C12-14-alkyl derivs.	129813-59-8	1 - 5	
Quartz (SiO2)	14808-60-7	0.1 - 1	

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Exposure to moisture during cure will release 0.1 - 0.9% methanol.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Wash with soap and water. If skin irritation persists, call a physician. Wipe off

paste with paper towel or cloth.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. If symptoms develop and

persist, get medical attention.

Ingestion: Do not induce vomiting. If a person feels unwell or symptoms of skin irritation

appear, consult a physician.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: carbon dioxide, foam, powder, water spray jet, fine water spray

Special firefighting procedures: Wear protective equipment. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: None identified.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for

large spills.

7. HANDLING AND STORAGE

Handling: Do not handle contact lenses until all sealant has been removed from hands.

Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing. Keep out of the reach of children. Protect from

moisture. Use only with adequate ventilation.

Storage: For safe storage, store between -20 °C (-4°F) and 50 °C (122°F)

Store in a cool, dry area. Avoid moisture.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None	None	None	None
Benzene, mono-C10-13-alkyl derivs.	None	None	None	None
Trimethoxyvinylsilane	None	None	None	None
Benzene, mono-C12-14-alkyl derivs.	None	None	None	None
Quartz (SiO2)	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not

sufficient to control airborne contamination below occupational exposure

limits

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:VariousOdor:AlcoholOdor threshold:Not available.pH:Not applicableVapor pressure:Not applicableBoiling point/range:Not applicableMelting point/ range:Not applicable

Melting point/ range:

Specific gravity:

Not applicable

1.4 - 1.5 at 20 °C (68°F)

Vapor density: Heavier than air.

Flash point: 107 °C (224.6 °F) Seta closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not applicable lnsoluble

Not available.

VOC content: 2.48 %; 36 g/l (by weight, calculated using CARB method; g/L less water, less

exempts calculated using SCAQMD method)

Viscosity: Not available.

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

Methanol is liberated slowly upon exposure to moisture.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Exposure to moisture.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May cause nose, throat and lung irritation. Abrasion of cured material such as by sanding or

grinding could release respirable particles of silica quartz, a cancer hazard by inhalation.

Normal use of this product causes no such release.

Skin contact:

Eye contact:
Causes skin irritation.
Causes serious eye irritation.
Ingestion:
May be harmful if swallowed.

Acute inhalation product

toxicity:

The substance or mixture has no acute inhalation toxicity.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	None	Irritant
Benzene, mono-C10-13-alkyl derivs.	None	No Data
Trimethoxyvinylsilane	Inhalation LC50 (Rat, 4 h) = 2773 ppm	Irritant, Allergen
Benzene, mono-C12-14-alkyl derivs.	None	No Data
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Phthalic acid, di(C9-11)alkylester, branched, C10-rich	No	No	No
Benzene, mono-C10-13-alkyl derivs.	No	No	No
Trimethoxyvinylsilane	No	No	No
Benzene, mono-C12-14-alkyl derivs.	No	No	No
Quartz (SiO2)	Known To Be Human	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Delayed Health, Immediate Health
None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm. This product contains a chemical known in the State of California

to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 3, 8, 11, 13

Prepared by: Product Safety and Regulatory Affairs

Issue date: 09/07/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.