file:///U//MSDS/Facilities/Housekeeping/whiteboard%20cleaner.htm

SANFORD CORPORATION -- EXPO WHITE BOARD CLEANER, CLEAR -- 7930-00F010059

Product ID: EXPO WHITE BOARD CLEANER, CLEAR MSDS Date:02/01/1990 FSC:7930 NIIN:00F010059 MSDS Number: BHRRN === Responsible Party === Company Name: SANFORD CORPORATION Address: 2740 WASHINGTON BLVD City: BELLWOOD State: IL ZIP:60104-1940 Country:US Info Phone Num: 800-228-5635 Emergency Phone Num: 800-228-5635 CAGE: E0365 === Contractor Identification === Company Name: SANFORD CORPORATION Address: 2740 WASHINGTON BLVD. Box:City:BELLWOOD State: IL ZIP:60104 Country:US Phone: 1-800-323-0749 CAGE:86874 Company Name: SANFORD CORPORATION Address: 2740 WASHINGTON BLVD City: BELLWOOD State: IL ZIP:60104 Country:US Phone: 1-800-323-0749 CAGE: E0365 ================= Ingred Name:WATER CAS:7732-18-5

RTECS #:2C0110000

file:///U//MSDS/Facilities/Housekeeping/whiteboard%20cleaner.htm

Ingred Name: ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL CARBINOL CAS:67-63-0 RTECS #:NT8050000 Other REC Limits:400 PPM OSHA PEL:400 PPM ACGIH TLV:400 PPM Ingred Name: 2-BUTOXYETHANOL (ETHYLENEGLYCOL MONOBUTYL ETHER), BUTYL CELLOSOLVE, BUTYL GLYCOL, GLYCOL ETHER EB CAS:111-76-2 RTECS #:KJ8575000 Other REC Limits: 25 PPM (SKIN) OSHA PEL:50 PPM (SKIN) ACGIH TLV:25 PPM (SKIN) Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: EYES: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Overexposure: EYES: IRRITATION. First Aid: EYES: FLUSH W/WATER. Flash Point Method:TCC Flash Point:105F Lower Limits:SEE SUPP Spill Release Procedures:WIPE UP W/ABSORBENT MATERIAL. Handling and Storage Precautions: THE PRODUCT IS CONSIDERED SAFE WHEN USED UNDER NORMAL USE CONDITIONS. USE IN A WELL VENTILATED AREA. Other Precautions: KEEP OUT OF REACH OF CHILDREN.

=============== Respiratory Protection: NONE UNDER NORMAL USE CONDITIONS. Ventilation:RECOMMENDED Protective Gloves: NONE UNDER NORMAL USE CONDITIONS Eye Protection: NONE UNDER NORMAL USE CONDITIONS Supplemental Safety and Health LOWER FLAMMABILITY LIMIT: 2.5 FOR ISOPROPANOL Boiling Pt:B.P. Text:180F Vapor Pres:33 Vapor Density:2 Spec Gravity:0.78 Evaporation Rate & Reference: (ETHER = 1): 7.7 Appearance and Odor: CLEAR LIQUID, CHARACTERISTIC ALCOHOL ODOR. Stability Indicator/Materials to Avoid:YES Waste Disposal Methods: DISCARD AS SOLID WASTE. Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department The United States of America in no manner whatsoever, of Defense. expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.